



**2010 Shasta Raceway Park Enduro  
General Rules, Eligibility, Purse, and Entry**

- 1.) All drivers must have a driver's license, or be a registered member of Shasta Raceway Park.
- 2.) All vehicles must pass a safety and tech inspection before racing.
- 3.) Transponders will be provided.
- 4.) A passenger is not required, however if the race is started without a passenger then the race must be finished without a passenger.
- 5.) Driver and **existing** passenger may switch at halfway break.
- 6.) Any driver found to be intentionally hitting or spinning other vehicles will receive a black flag and must exit the track. Failure to obey black flag will result in disqualification.
- 7.) All vehicles must be removed from the track after the event.

**Race Procedures**

- 1.) Starting position will be determined by random drawing.
- 2.) Scoring will be determined by total laps completed at the conclusion of race. 200 laps or 2 hours whichever comes first.
- 3.) All vehicles will be allowed a practice session to ensure transponder is properly working.
- 4.) A 15-minute break will occur at the halfway point in the race.
- 5.) All vehicles must stay in position, exit the track, and line up along pit entrance as directed for halfway break.
- 6.) Vehicles are not allowed to return to pit stall during halfway break. Violation will result in a 5-lap penalty.
- 7.) Refueling and repairs may be made at halfway break.
- 8.) A yellow flag will be displayed only in the event of a driver/passenger safety compromise.
- 9.) Disabled vehicles will be removed from the track only during yellow or red flag conditions.

Purse

<b>1<sup>st</sup> \$1000</b>	<b>2<sup>nd</sup> \$500</b>	<b>3<sup>rd</sup> \$300</b>
<b>4<sup>th</sup> \$200</b>	<b>5<sup>th</sup> \$150</b>	<b>6<sup>th</sup>-10<sup>th</sup> \$100</b>

**Pre Entry Fee is \$60 includes 4 grandstand tickets (Deadline is Wed. Feb. 3rd 2010)  
Entry Fee at the gate on race day is \$75, Pit passes are \$30**

**2010 Shasta Raceway Park Enduro Entry Form**

Send Entry & Check to: *Shasta Raceway Park, 20 La Colina Terrace, Anderson, CA. 96007*

\* MUST BE RECEIVED BY 5:00PM, Wed. Feb. 3rd 2010

NAME: \_\_\_\_\_ CAR # \_\_\_\_\_  
 ADDRESS: \_\_\_\_\_ APT # \_\_\_\_\_  
 CITY: \_\_\_\_\_ ST: \_\_\_\_\_ ZIP: \_\_\_\_\_  
 PHONE: (\_\_\_\_) \_\_\_\_\_ SSN # \_\_\_\_\_  
 EMAIL: \_\_\_\_\_

AMT PAID: \$ \_\_\_\_\_ No Visa/MC, Check Only, Thanks



## **2010 Shasta Raceway Park Enduro Rules**

### **Competing Models**

1. Open to any medium or full sized car, pick-up, or van.
2. Max ¾ ton pick-up or van. No duels.
3. 4-wheel drive ok, front driveline must be removed.
4. Open to all bomber cars.

### **Body Requirements**

1. Body must remain stock.
2. Stock bumpers must be used front and rear and must be chained to cage or frame.
3. Doors must be welded or chained shut.
4. Skinning of sheet metal is permitted.
5. Hood latches must be removed and hood secured with at least 1 pin for fire access.
6. Interior must be stripped of all combustible material, with the exception of the front seats.
7. Stock headlamps, tail and marker lamps must be removed.
8. Door panels may be removed for door bars. Door bars must extend out to the door skin if panel is removed.
9. All glass must be removed with the exception of the front windshield.
10. Windshield may be replaced with wire mesh or lexan. Must have one of these at all times during race.
11. If using mesh or lexan must have at least 1 metal windshield strap minimum of 3/4"x1/4" or 1"x1/8" located in center of windshield.
12. All floorboards, front and rear firewalls must be completely sealed from the rest of the vehicle with exception of transponder hole.
13. No oil or fuel allowed to run through the cockpit area.
14. Any type stock rear end.
15. Driveline must be strapped with hoop or chained.
16. Any stock steel 7" or 8" wheel permitted.
17. Any D.O.T. approved vehicle tire permitted.
18. All studs and lug nuts must be present.
19. Transponders must be mounted inside the vehicle cockpit no higher than 11" from track surface with unobstructed view of track.
20. Car numbers must be at least 18" tall in contrasting colors.
21. Decorating of vehicle is permitted.

### **Engine Requirements**

1. Exhaust must exit past the driver.
2. Radiator must be mounted in stock location.
3. NO anti-freeze allowed.
4. Carburetor must have two return springs.
5. Any battery located in the cockpit area must be secured and covered.

### **Roll Cage**

1. All vehicles must be equipped with four-point roll cage.  
Includes 4 uprights with top halo.  
Material must be minimum of 1-1/2-inch roll bar tubing of .090 wall thickness or 1.66 OD black steel pipe of .120 wall thickness.
2. Must have 1 diagonal bar behind seat from top corner to bottom opposite.
3. Must have one dash bar across front of roll cage.
4. Cage must have at least 1 door bar on drivers and passenger's side.
5. If only one door bar then must connect from rear upright at shoulder height to front bottom.
6. All joints must be gusseted and completely welded.
7. Main cage must have at least 1 bar from top of cage to rear frame or trunk floor.
8. Cage must be welded directly to frame or welded to 6x6x1/4" plates secured to floor with at least 4 grade 5- 3/8 bolts.
9. All accessible cage must be padded.

### **Safety Equipment**

1. Fuel cells are allowed.
2. Stock fuel tanks may be removed and located in trunk of passenger cars.  
Must be strapped with (4) steel straps. 3/32-"by 1-"material if located in trunk area.
3. All drivers and passengers must be fully clothed.
4. All safety rules for driver will be for passenger also.
5. No tank tops, short sleeve shirts, shorts, or open toe shoes will be permitted.
6. Fire resistant clothing is highly recommended.
7. All vehicles must have an on board fully charged fire extinguisher accessible to driver and passenger.
8. Driver and passenger helmets are required.
9. Approved helmets will be SA 2000 standard snell and or SFI 31.1 or 31.2 sticker.
10. **M rated helmets will be permitted.**
11. All vehicles must have at least the proper working stock safety belt system.
12. Racing harness is highly recommended
13. No bench or 60/40 seats allowed. Any style Bucket, Baja and any approved race seat will be permitted.
14. Window nets are mandatory. Must be permanently secured at bottom with quick release at the top.