



2010 Shasta Raceway Park Street Stock Spectacular Rules

\$400 to win and guaranteed \$50 to start feature with a minimum of 14 car field.

July 17th and September 25th, 2010

Models: Open to 1960 to 2009 American made mid or full-size passenger cars. Stock, steel or stock appearing body panels only, in stock location.

Weight: 3,250 lbs car and driver. Maximum left side weight is 56%.

Chassis: Frames must be OEM. Stock front and rear OEM sub-frames must be used on Unibody cars. Sub-frame connectors okay.

Suspension:

- 1) All suspension mounting brackets must be of original configuration, stock components, and in stock location unless otherwise noted.
- 2) Any steel spring 5" in diameter minimum. No coil overs.
- 3) Any steel non-adjustable shock mounted in the stock position. No heim ends allowed on shocks.
- 4) Leaf spring cars may use lowering blocks. Aftermarket leaf springs allowed.
- 5) OEM Spindles, lower A-frames, and hubs only.
- 6) Upper A-frames may be aftermarket, but must mount in stock location.

Roll Cage: A conventional perimeter framed stock car roll cage is mandatory. Main roll cage should be constructed of 1-3/4 inch x .095 wall thick round magnetic tube.

Engines:

- 1) Maximum 360 c.i. for Chevy and Ford. Maximum 368 c.i. for AMC and Dodge. No aluminum blocks or heads.
- 2) GM crate motor #88958602 with in-tact factory bolts in place is allowed.
- 3) No after-market performance heads. No Vortec heads. Stock replacement heads allowed. No porting or polishing of any kind.
- 4) Aluminum intake manifolds allowed. No porting, polishing, grinding, or modifications.
- 5) Solid or hydraulic lifters allowed. No roller lifters.
- 6) Screw-in studs, roller rockers, and stud girdles are allowed.
- 7) Wet sump oiling systems only.

Carburetor: One 500 cfm Holley 4412 carburetor shall be used. Exception: crate motor option allowed one 650 cfm 80541-1 or one 750 cfm 80508-2 Holley.

Exhaust: Mufflers and exhaust shall be used on all race cars entering the track. Max 95 dba @ 100 ft.

Drive Train: Third member may be locked using a spool only. No limited slip or ratcheting type lockers.

Wheels: Steel maximum 8-inch. Offset wheels are allowed.

Tires: Goodyear D2862 or D2863.

No traction control devices allowed

Transponders are mandatory for scoring and available for rent (\$20).

Officials Decision's are final.

Rick Faeth

Shasta Raceway Park

(408) 499-6845

email: bcra91@netzero.net